



# SecuMate Mini Portable Security Recorder

## Features

- MPEG4 compression
- Portable and compact size
- Video loss auto detection
- Audio recording
- Adjustable sensitivity and area selectable for motion detection
- Three levels image quality
- Backup ASF file format with time stamp
- Record mode: Manual / Continuous / Motion Detection
- Independent frame rate for each recording mode
- Support SD card
- DC5V or 2xAA Batteries



## Storage Capacity :

Unit: minutes

Quality Level	704x240@24 IPS	352x240@30 IPS
High	64	160
Medium	128	320
Low	192	480

(Approx. for recording motion movie with 1GB Card)

Model No.		RYK-9122
Video	System	NTSC / PAL with Video Loss Auto Detection
	Codec	MPEG4-SP ASF File Format
	Recording Frame Rate	704x480@12 IPS, 352x240@30 IPS (NTSC) 704x560@10 IPS, 352x280@25 IPS (PAL)
	Recording Quality	High / Medium / Low
	Recording Date / Time	Overlay with Video Images in ASF File
	Input	1 CH, Phone Jack
	Output	1 CH, Phone Jack
Audio	Sampling Rate	44.1 KHz
	Codec	G.726 / 32 kbps
	Input	1 CH, Phone Jack
	Output	1 CH, Phone Jack
Storage Media	Secure Digital (SD) Card	
Recording Mode	Schedule / Motion Detection / Manual	
Motion Detection Setting	Multiple Blocks and adjustable sensitivity	
Playback Function	Play / Fast Forward / Fast Rewind / Pause / Step Forward / Step Rewind	
Playback Speed	x1 / x2 / x4 / x8 / x16 / x32	
Power Supply	AC100~240V 50/60 Hz, DC5V / 1A or AAx2 Batteries Rechargeable Ni-MH / Alkaline Battery / CR-V3 / RCR-V3	
Power Consumption	2.5W max.	
Weight	150 g (without Battery)	
Dimensions (WxHxD)	65x90x27 mm	
Operating Environment	30~80% RH, 5°C ~ 40°C (41°F ~ 104°F)	

■ IPS: Images Per Second